



**Combustible, Toxic and
Oxygen gas detector for
industrial applications**

Sensepoint XCD



One-Stop Shop

- Combustible (catalytic or infrared), toxic and Oxygen versions available
- New and retrofit applications
- Suitable for indoor or outdoor use
- Stainless steel or aluminium explosion-proof housing options
- IP66 as standard

Proven and Reliable Sensor Technology

- Surecell™ electrochemical sensors
- Reflex® sensor health check
- Poison immune infrared sensors
- Poison resistant catalytic bead sensors
- Long life sensors

Global Approvals

- US and Latin America, European, Canadian and Asian
- Compliant with UL, INMETRO, ATEX, IECEx, CSA, KTL, PA, GB, and CCCF standards

Easy to Use

- User friendly and intuitive tri-colour backlit display with digits, bar graph and icons
- Fully configurable via magnetic switches
- Selectable sink or source 4-20mA output
- Auto-inhibit during maintenance
- MODBUS communications

Cost Effective

- Common transmitter platform
- Minimal training required
- Reduced spares
- Non-intrusive, one-man operation
- Plug-in sensor replacement
- MODBUS multi-drop option offers cabling savings

Simple Installation

- Plug-in display module removes to provide access to terminal area
- Integral mounting bracket
- 2 x M20 or ¾" NPT cable/conduit entries (certification dependent)
- Removable plug/socket type terminal blocks for ease of wiring
- Sink/source switch to suit preferred wiring topology

Range of Optional Accessories

- Remote sensor gassing kit
- Duct mounting kit
- Calibration gas flow housing
- Collecting cone

Sensepoint XCD provides comprehensive monitoring of combustible, toxic and Oxygen gas hazards in potentially explosive atmospheres, both indoors and outdoors. Users can modify detector operation using the LCD and magnetic switches without ever needing to open the unit. This enables one-man, non-intrusive operation and reduces routine maintenance time and costs.

A tri-colour backlit LCD clearly indicates the unit's status at a glance, even from a distance. A steady green backlight indicates normal operation, flashing yellow indicates fault and flashing red indicates an alarm.

All detectors include two programmable alarm relays, one programmable fault relay and an industry standard 4-20mA output (sink or source selectable). Modbus comes optional.

Sensepoint XCD's operation can be modified using the transmitter's LCD and non-intrusive magnetic switches. Outputs are automatically inhibited during adjustment, thereby reducing the risk of false alarm at the control panel during maintenance.

Sensepoint XCD's remote sensing capabilities allow the sensor to be mounted up 100 feet (30m) away from the transmitter in areas that are difficult to access. The transmitter can be mounted at a suitable location away from this area where it is easy to access, view its display and interact with via the user interface.

Sensepoint XCD has an integral mounting plate for surface mounting or can be mounted to a horizontal or vertical pipe using the optional pipe mounting bracket. Electrical installation can be made using either conduit or cable with suitable mechanical protection. Two M20 or ¾"NPT entries are provided (depending on certification). A weatherproof cap is also included for use in the harshest outdoor conditions. Other optional accessories include a sunshade/deluge protection, duct mounting kit and collecting cone.

Sensepoint XCD ensures easy installation and the fastest routine operation by removing the need for hot work permits in hazardous areas. Using easy to replace plug-in sensors, downtime is also reduced and ongoing costs are minimized through the use of poison resistant flammable sensors, poison immune infrared Hydrocarbon sensors and patented Surecell™ toxic sensors and Reflex® sensor health check.




Sensepoint XCD Overview



Sensepoint XCD Gases and Ranges					
Gas	User Selectable Full Scale Range	Range Increments	Class I, Division 1	Class I, Division 2	Remote Capability
Combustible Sensors					
Flammable 1 to 8*	20 to 100%LEL	10%LEL	✓		
Methane	20 to 100%LEL	10%LEL	✓		
Propane	20 to 100%LEL	10%LEL	✓		
Carbon Dioxide	2%Vol.	0.1%Vol.	✓		
Toxic Sensors					
Hydrogen Sulfide	10 to 100ppm	0.1ppm	✓		
	50ppm	N/A		✓	✓
Carbon Monoxide	100 to 1,000ppm	100ppm	✓		
	200ppm	N/A		✓	✓
Hydrogen	1,000ppm	N/A	✓		
	1,000ppm	N/A		✓	✓
Nitrogen Dioxide	10 to 50ppm	5ppm	✓		
	10ppm	N/A		✓	✓
Ammonia	50ppm	N/A		✓	✓
Chlorine	5ppm	N/A		✓	✓
Sulphur Dioxide	15ppm	N/A		✓	✓
Nitric Oxide	100ppm	N/A		✓	✓
Oxygen Sensors					
Oxygen	25%V/V	N/A	✓		
	25%V/V	N/A		✓	✓

Sensepoint combustible, toxic and Oxygen sensors offer a wide variety of gases and measuring ranges. The sensor can be mounted directly to the transmitter or remotely. Sensepoint XCD can be used as a common platform for all toxic and Oxygen gas detection, reducing maintenance. The Sensepoint sensor design includes an IS portion with a removable sensor cartridge, eliminating the need for a hot work permit when changing the sensor cartridge. The sensor has an IP66 rating for use in the harshest conditions. The maximum distance between the transmitter and the remote sensor is 100 ft. (30m).



Sensepoint XCD Class I, Division 1



Sensepoint XCD Class I, Division 2



Sensepoint XCD Class I, Division 2 with Remote Sensor

Safety at a Glance!

Sensepoint XCD uses three instantly recognizable 'traffic light' colors to indicate its status. The large tri-color backlit LCD is steady green to indicate normal operation, flashes yellow to indicate a fault/warning and flashes red to indicate an alarm. This allows anyone in the area to clearly see *at a glance* the status of any detector. This can be particularly useful to identify detector status if the detector is located in a difficult to access area or if a number of detectors are located in the same area.



XCD is the right choice for a variety of demanding industrial applications

Building Environment	Specific Area	Gases Present (Detected by XCD)
 Chemical Plants	<ul style="list-style-type: none"> Raw material storage Process Areas Laboratories Pump rows Compressor stations Loading/unloading areas 	<ul style="list-style-type: none"> Ethylene Hydrogen Hydrogen Sulfide Methane Oxygen Propane
 Oil & Gas	<ul style="list-style-type: none"> Exploration drilling rigs Production platforms Onshore oil and gas terminals Refineries 	<ul style="list-style-type: none"> Carbon Dioxide Carbon Monoxide Hydrogen Hydrogen Sulfide Methane Oxygen Propane
 Power Stations	<ul style="list-style-type: none"> Around the boiler pipework and burners Turbines Coal silos and conveyor belt areas in older coal/oil fired stations 	<ul style="list-style-type: none"> Carbon Monoxide Hydrogen Methane Oxygen
 Waste Water Treatment Plants	<ul style="list-style-type: none"> Digesters Plants sumps H₂S scrubbers Pumps 	<ul style="list-style-type: none"> Carbon Monoxide Hydrogen Sulfide Methane Nitrogen Dioxide Oxygen
 Steel Industry	<ul style="list-style-type: none"> Loading and unloading Pre-treatment Blast furnace 	<ul style="list-style-type: none"> Carbon Dioxide Carbon Monoxide Methane Oxygen
 General Industry	<ul style="list-style-type: none"> Battery rooms Loading and unloading docks Process areas Machinery rooms 	<ul style="list-style-type: none"> Carbon Monoxide Methane Oxygen Propane

Find out more

www.honeywellanalytics.com

Contact Honeywell Analytics:

Americas

Honeywell Analytics, Inc.
405 Barclay Blvd.
Lincolnshire, IL 60069
USA

Tel: 847.955.8200
Toll-free: 800.538.0363
Fax: 847.955.8210
detectgas@honeywell.com

Technical Services

ha.service@honeywell.com

www.honeywell.com

Europe, Middle East, Africa

Life Safety Distribution AG
Weiherallee 11a
CH-8610 Uster
Switzerland

Tel: +41 (0)44.943.4300
Fax: +41 (0)44.943.4398
gasdetection@honeywell.com

Honeywell Analytics Serves Every Business

We offer the industry's most complete range of gas detection products and services to meet all customer needs.

Commercial

Gas detection from standalone units to fully engineered, multi-point systems, all offering cost-effective regulatory compliance

» Applications: parking structures, chillers, mechanical rooms, office towers, commercial buildings, shopping centers, swimming pools, golf courses, schools and universities, laboratories

Industrial

Renowned Sieger, Zareba and Manning gas detection systems with advanced electrochemical, infrared and open path sensing technologies

» Applications: oil and gas, cold storage, water/wastewater treatment, chemicals, engine rooms, plastics and fibers, agriculture, printing and light industrial

Portables

Single or multi-gas BW Technologies, Lumidor and other premium detectors with compact, lightweight designs ranging from simple alarm only units to advanced, fully configurable and serviceable instruments

» Applications: underground utility and electricity ducts, boiler rooms, post-fire sites, sewers, industrial plants, industrial hygiene, first responder teams, remote fleets

High Tech/Government

A complete portfolio of gas and chemical detection instrumentation including infrared spectroscopy with no cross interference (MST Technologies), to Chemcassette paper-based solutions (MDA Scientific) offering detection down to parts per billion

» Applications: semiconductor manufacturing and nanotechnology, aerospace propulsion and safety, specialty chemicals industry, research laboratories, emergency response

Technical Services

24/7 global network includes post-sales service and Systems Integration teams

» Emergency call out, service contracts, on/off-site repair, training and commissioning
» Complete range of spares, consumables and accessories

Asia Pacific

Honeywell Analytics, Asia Pacific
#508, Kolon Science Valley (1)
187-10 Guro-Dong, Guro-Gu
Seoul, 152-050

Korea
Tel: +82 (0)2.2025.0307

Fax: +82 (0)2.2025.0329
analytics.ap@honeywell.com

Honeywell